**ENGINE** C9.3 ATAAC

Agrisynth MSP 10W-40

**HYDRAULIC CAB TILT SYSTEM** 

## CATERPILLAR FOREST HARVESTERS 568 LL YJX/BRB (2011 AND AFTER)



Capacity: 32 liter		
use Normal		CLIMATE
		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	
Check every 10 hours, change every 3	months/ 500 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30	
Check every 10 hours, change every 3	months/ 500 hours	
USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Alternative (acceptable)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agridiesel MSP 15W-40	Dieselfleet LSP Ultra 10W-30

**Dieselfleet MSP 15W-40** 

Check every 10 hours, change every 3 months/ 500 hours

Capacity: 7,2 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 20	00 hours/ 12 months	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 10W	Perlus Biosynth 46	
Check every 10 hours, change every 20	00 hours/ 12 months	·



HYDRAULIC SYSTEM Capacity: 194 liter (Refill)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	
Check every 10 hours, change every	18 months/ 3000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check every 10 hours, change every	18 months/ 3000 hours	
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
Check every 10 hours, change every	18 months/ 3000 hours	,

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
Check every 50 hours	

COOLING SYSTEM Capacity: 35 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		
Check every 10 hours, change ever	72 months/ 12000 hours	,



SWING GEAR Capacity: 35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Check every 12 months/ 2000 hours		
SWING REDUCTION UNIT Capacity: 19 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Change every 250 hours		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Change every 250 hours		



<b>SWING REDUCTION UNIT HIGH SWING</b> Capacity: 10 liter (each)	TORQUE	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/250 hours, change	every 6 months/ 1000 hours	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	Gear Oil Alcat 50	
Check every 1 months/ 250 hours, change	every 12 months/ 2000 hours	
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	every 12 months/ 2000 hours	



TRAVEL REDUCTION UNIT Capacity: 8 liter (each)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Check every 1 months/ 250 hours, chang	ne every 12 months/2000 hours		
USE		CLIMATE	
Normal		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Check every 1 months/ 250 hours, chang	ne every 12 months/2000 hours		
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gear Oil Alcat 30	Gear Oil Alcat 50		
Change every 250 hours/ 6 months			
USE		CLIMATE	
Initial service		Arctic	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Change every 250 hours/ 6 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.