## CATERPILLAR TRACKED EXCAVATORS 235 81X (1973-1986)



ENGINE Capacity: 27 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Change every 250 hours/ 1 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40
Change every 250 hours/ 1 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours/ 1 months		
FINAL DRIVES Capacity: 53 liter (each side)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
HYDRAULIC SYSTEM Capacity: 329 liter		
JSE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 3 months/ 500 hours, ch	ange every 12 months/ 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

## CATERPILLAR TRACKED EXCAVATORS 235 81X (1973-1986)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 44 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 17	

Check every 3 months/ 500 hours, change every 12 months/ 2000 hours

CLAMSHELL ROTATOR GEAR DRIVE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

PUMP DRIVE Capacity: 6,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Change every 2000 hours/ 12 months	

SWING GEAR Capacity: 38 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Check every 12 months/ 2000 hours	

## CATERPILLAR TRACKED EXCAVATORS 235 81X (1973-1986)



SWING REDUCTION UNIT Capacity: 34 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	
Check every 1 months/ 250 hours	

TRACK PINS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

TRACK ROLLERS & IDLERS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.