

CATERPILLAR TRACKED EXCAVATORS

320B 1XS (1996-2001)



ENGINE 3116T
Capacity: 21,5 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Change every 250 hours/ 1 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40

Change every 250 hours/ 1 months

FINAL DRIVES
Capacity: 8 liter (each hub)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2
Gear Oil Alcat 50

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE
Normal

CLIMATE
Arctic

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 10W

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2
Gear Oil Alcat 50

Change every 250 hours

USE
Initial service

CLIMATE
Arctic

PRODUCT RECOMMENDATION 1
Gear Oil Alcat 10W

Change every 250 hours

CATERPILLAR TRACKED EXCAVATORS

320B 1XS (1996-2001)



HYDRAULIC SYSTEM

Capacity: 235 liter (System), Capacity: 120 liter (Tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agridiesel CRD+ 15W-40	Agrifluid Synth XHP Ultra

Check every 1 months/ 250 hours, change every 12 months/ 2000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

Capacity: 1,5 liter (Reservoir), Capacity: 29 liter (System)

USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Change every 6000 hours/ 72 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Change every 24 months/ 3000 hours

SWING GEAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 12 months/ 2000 hours

CATERPILLAR TRACKED EXCAVATORS

320B 1XS (1996-2001)



SWING REDUCTION UNIT

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 50*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 50*Change every 250 hours*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Change every 250 hours*

TRACK IDLERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

TRACK ROLLERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.