

| ENGINE 3116T Capacity: 21,5 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |
| Check every 10 hours, change every 1 months/250 hours | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Synfleet SHPD 10W-40 | Multifleet SHPD 10W-40 | |

Check every 10 hours, change every 1 months/ 250 hours

| FINAL DRIVES Capacity: 10 liter | | |
|---|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Check every 1 months/250 hours, change | every 12 months/ 2000 hours | |
| USE | | CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Check every 1 months/ 250 hours, change every 12 months/ 2000 hours | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |
| Change every 250 hours | | |
| USE | | CLIMATE |
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Change every 250 hours | | |
| | | |

HYDRAULIC SYSTEM

Capacity: 141 liter (Hydraulic tank), Capacity: 265 liter (System)



| use Normal | | climate Mediterranean |
|---|---|--|
| PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 | | |
| Check every 10 hours, change every 2000 | hours/ 12 months | |
| use Normal | | climate Moderate |
| PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 | PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40 | PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra |
| Check every 10 hours, change every 2000 |) hours/ 12 months | |
| use Up to 50% hammer use | | climate Mediterranean |
| PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 | | |
| Check every 10 hours, change every 1000 | hours/ 12 months | |
| use Up to 50% hammer use | | climate Moderate |
| PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 | PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40 | PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra |
| Check every 10 hours, change every 1000 | hours/ 12 months | |
| use Continuous hammer use | | climate Mediterranean |
| PRODUCT RECOMMENDATION 1 Gear Oil Alcat 30 | | |
| Check every 10 hours, change every 600 l | hours/ 12 months | |
| use Continuous hammer use | | climate Moderate |
| PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40 | PRODUCT RECOMMENDATION 2 Agridiesel CRD+ 15W-40 | PRODUCT RECOMMENDATION 3 Agrifluid Synth XHP Ultra |
| Check every 10 hours, change every 600 l | hours/ 12 months | |
| | | |
| GREASE POINTS/NIPPLES | | |
| use Normal | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 HT Q9 High Grade Grease | PRODUCT RECOMMENDATION 2 | |

Change every 10 hours



| COOLING SYSTEM Capacity: 31,5 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant SP 17 | |
| | |

Check every 10 hours, change every 72 months/ 6000 hours

| SWING GEAR Capacity: 18,7 liter | | |
|------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Change every 2000 hours/ 12 months

| SWING REDUCTION UNIT Capacity: 8 liter | | |
|---|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | CLIMATE |
|--------------------------|---------|
| Normal | Arctic |
| PRODUCT RECOMMENDATION 1 | |
| Gear Oil Alcat 10W | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| use Initial service | | climate Moderate |
|--------------------------|--------------------------|---------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Change every 250 hours

| USE | CLIMATE |
|--------------------------|---------|
| Initial service | Arctic |
| PRODUCT RECOMMENDATION 1 | |
| Gear Oil Alcat 10W | |
| Change every 250 hours | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the



information contained herein is subject to changes without notification.