

CATERPILLAR MINI EXCAVATORS 305C CR GYZ/HWJ (2005-2010)



ENGINE Mitsubishi S4Q2
Capacity: 7 liter

USE		CLIMATE
Extended drain (max)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynt LSP 10W-40	Multifleet SHPD 10W-40	

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Change every 250 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Synfleet SHPD 10W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 10W-40

Change every 250 hours

FINAL DRIVES

USE		CLIMATE
Flexible (max)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube Racing 75W-140	SP Gear 1011	Syngear TDL 75W-90

CATERPILLAR MINI EXCAVATORS 305C CR GYZ/HWJ (2005-2010)



HYDRAULIC SYSTEM

Capacity: 48 liter (Hydraulic tank), Capacity: 78 liter (Total)

USE		CLIMATE
Flexible (max)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Gear Oil Alcat 30	

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar 0W-40	Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

USE		CLIMATE
Light Duty		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

CATERPILLAR MINI EXCAVATORS 305C CR GYZ/HWJ (2005-2010)



COOLING SYSTEM

Capacity: 11 liter

USE	CLIMATE
Extended	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Change every 6000 hours/ 72 months*

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Change every 12000 hours/ 72 months*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF*Change every 24 months/ 3000 hours*

USE	CLIMATE
Acceptable	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF*Change every 36 months/ 3000 hours*

SWING REDUCTION UNIT

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 50

USE	CLIMATE
Flexible (max)	Arctic

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W

CATERPILLAR MINI EXCAVATORS 305C CR GYZ/HWJ (2005-2010)



TRACK IDLERS

USE		CLIMATE
Flexible (max)		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

TRACK ROLLERS

USE		CLIMATE
Flexible (max)		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.