

# CATERPILLAR WHEELED EXCAVATORS

## 214

**ENGINE**

Capacity: 14 liter

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Multifleet SCD 40****PRODUCT RECOMMENDATION 2****Multifleet SCD 30***Check every 10 hours, change every 1 months/ 250 hours***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Synfleet SHPD 10W-40***Check every 10 hours, change every 1 months/ 250 hours***USE**

Normal

**CLIMATE**

Cold

**PRODUCT RECOMMENDATION 1****Multifleet SCD 10W***Check every 10 hours, change every 1 months/ 250 hours***DIFFERENTIAL STEERED AXLE**

Capacity: 10 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Change every 2000 hours/ 12 months***HUB REDUCTIONS**

Capacity: 1,5 liter (each hub)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Change every 2000 hours/ 12 months*

# CATERPILLAR WHEELED EXCAVATORS

## 214



### TRANSAXLE

Capacity: 13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 2000 hours/ 12 months*

### HYDRAULIC SYSTEM

Capacity: 270 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 10 hours, change every 2000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 10 hours, change every 2000 hours/ 12 months*

### GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2**

### AXLE STABILIZERS

Capacity: 2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Change every 2000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Change every 2000 hours/ 12 months*

# CATERPILLAR WHEELED EXCAVATORS

## 214



### SWING DRIVE UNIT

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>SP Gear 1011</b>	<b>Syngear TDL 75W-90</b>	<b>Gearlube GL-5 80W-90</b>

*Change every 2000 hours/ 12 months*

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>SP Gear 5015</b>	<b>SP Gear 1071</b>	

*Change every 2000 hours/ 12 months*

### SWING GEAR BRAKE SYSTEM

Capacity: 35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-S DOT 4</b>		

*Check every 1 months/ 250 hours*

### TRAVEL BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid-S DOT 4</b>		

*Check every 1 months/ 250 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.