CATERPILLAR WHEELED EXCAVATORS224



ENGINE Capacity: 16 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 40	Multifleet SCD 30	
Change every 250 hours/ 1 months	•	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Synfleet SHPD 10W-40
Change every 250 hours/ 1 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 250 hours/ 1 months		
	<u> </u>	

DIFFERENTIAL STEERED AXLE Capacity: 10,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 500 hours, change every 12 mor	ths/ 2000 hours

HUB REDUCTIONS Capacity: 2-2,7 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Check every 500 hours, change every 12 i	onths/ 2000 hours	

Gear Oil Alcat 10W

Check every 500 hours, change every 12 months/ 2000 hours

CATERPILLAR WHEELED EXCAVATORS224



TRANSAXLE Capacity: 0-0 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 500 hours, change eve	v 12 months/ 2000 hours

HYDRAULIC SYSTEM Capacity: 300 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 500 hours, change every 12 i	months/ 2000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		

GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

RODUCT RECOMMENDATION 1	
Gear Oil Alcat 30	
SE	CLIMATE
Jormal	Moderate

CATERPILLAR WHEELED EXCAVATORS 224



SWING DRIVE UNIT Capacity: 8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011 Syngear TDL 75W-90		Gearlube GL-5 80W-90
Check every 500 hours, change every 1	2 months/ 2000 hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1071		
Check every 500 hours, change every 1	2 months/ 2000 hours	

SWING GEAR BRAKE SYSTEM Capacity: 350 CM3	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	

TRAVEL BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.