

CATERPILLAR MOTOR GRADERS 16M R9H

(2007 AND AFTER)



ENGINE C13 Acert
Capacity: 30 liter

USE	CLIMATE
Preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth MSP 5W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agridiesel MSP 15W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 3 months/ 500 hours

TANDEM DRIVE

Capacity: 127 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION Powershift
Capacity: 100 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gear Oil Alcat 30	Gear Oil Alcat 50

Check every 10 hours, change every 6 months/ 1000 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	
Gear Oil Alcat 10W	

Check every 10 hours, change every 6 months/ 1000 hours

CATERPILLAR MOTOR GRADERS 16M R9H

(2007 AND AFTER)



HYDRAULIC SYSTEM

Capacity: 64 liter (Hydraulic tank)

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 10 hours, change every 24 months/ 4000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 10W*Check every 10 hours, change every 24 months/ 4000 hours*

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1

Perlus Biosynth 46*Check every 10 hours, change every 24 months/ 4000 hours*

WHEEL SPINDLE BEARING FRONT

Capacity: 0,9 liter (each wheel)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30

PRODUCT RECOMMENDATION 2

Gear Oil Alcat 50*Check every 3 months/ 500 hours, change every 24 months/ 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 3 months/ 500 hours, change every 24 months/ 2000 hours*

COOLING SYSTEM

Capacity: 49 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 17*Check every 10 hours, change every 36 months/ 6000 hours*

CATERPILLAR MOTOR GRADERS 16M R9H (2007 AND AFTER)



CIRCLE DRIVE GEARBOX

Capacity: 7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.