

CATERPILLAR MULTI TERRAIN LOADERS

257B CATERPILLAR 3024CT (2003-2008)



ENGINE 3024C T
Capacity: 7,5 liter

| USE | CLIMATE |
|-----------|---------------|
| Preferred | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 500 hours/ 12 months

| USE | CLIMATE |
|-----------|----------|
| Preferred | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|-------------------------------|--|
| Agrisynth LSP 10W-40 | Multifleet SHPD 10W-40 | |

Check every 10 hours, change every 500 hours/ 12 months

| USE | CLIMATE |
|--------------------------|---------------|
| Alternative (acceptable) | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|-------------------------------|--|
| Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 | |

Check every 10 hours, change every 500 hours/ 12 months

| USE | CLIMATE |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-------------------------------|-------------------------------|
| Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 10W-40 |

Check every 10 hours, change every 500 hours/ 12 months

HYDRAULIC SYSTEM
Capacity: 35 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Gear Oil Alcat 30 | | |

Check every 10 hours, change every 2000 hours/ 12 months

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 2000 hours/ 12 months

CATERPILLAR MULTI TERRAIN LOADERS

257B CATERPILLAR 3024CT (2003-2008)

**COOLING SYSTEM**

Capacity: 10,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 17***Check every 10 hours, change every 72 months/ 12000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.