

CATERPILLAR MULTI TERRAIN LOADERS

297C CATERPILLAR C3.4 DIT (2007-2011)



ENGINE C3.4 DIT
Capacity: 10 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40

Check every 10 hours, change every 500 hours/ 12 months

FINAL DRIVES
Capacity: 1 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2
Unigear LS GL-3/GL-5 85W-140

Check every 250 hours, change every 500 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube Racing 75W-140

PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 3
Unigear HS GL-3/GL-5 80W-90

Check every 250 hours, change every 500 hours

USE
Initial service

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2
Unigear LS GL-3/GL-5 85W-140

Change every 250 hours

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube Racing 75W-140

PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 3
Unigear HS GL-3/GL-5 80W-90

Change every 250 hours

CATERPILLAR MULTI TERRAIN LOADERS

297C CATERPILLAR C3.4 DIT (2007-2011)



HYDRAULIC SYSTEM

Capacity: 42 liter, Capacity: 57 liter (System)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

Check every 10 hours, change every 2000 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT

Check every 10 hours, change every 2000 hours/ 12 months

COOLING SYSTEM

Capacity: 13,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

Check every 10 hours, change every 72 months/ 12000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.