

ENGINE 3054C T Capacity: 7,2 liter		
USE		CLIMATE
Preferred		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40	

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Preferred		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Armado Synth MSP 5W-40	Dieselfleet LSP Ultra 10W-30	Dieselfleet MSP 10W-30

Check every 10 hours, change every 3 months/ 500 hours

USE		CLIMATE
Alternative (acceptable)		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth MSP 10W-40	Dieselfleet MSP 15W-40	

Check every 10 hours, change every 3 months/ 500 hours

Agrisynth LSP Ultra 10W-40	Agridiesel MSP 15W-40	Armado Synth LSP Ultra 10W-40
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Alternative (acceptable)		Moderate
USE		CLIMATE

Check every 10 hours, change every 3 months/ 500 hours



DIFFERENTIAL FRONT Capacity: 11 liter			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 50			
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours			
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours			

DIFFERENTIAL REAR

Capacity: 24 liter, Capacity: 0,5 liter (special additive)

We are unable to give a standard recommendation for this component. Please contact our service department.

FINAL DRIVES FRONT Capacity: 0,7 liter (each side)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 50			
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 30			
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours			
USE		CLIMATE	
Normal		Cold	
PRODUCT RECOMMENDATION 1			
Gear Oil Alcat 10W			
Check every 1 months/ 250 hours, change every 6 months/ 1000 hours			



FINAL DRIVES REAR Capacity: 1,6 liter (each side)		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 1 months/ 250 hours, change	e every 6 months/ 1000 hours	
TRANSMISSION Capacity: 18,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 50		
Check every 10 hours, change every 6 mg	onths/ 1000 hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		
Check every 10 hours, change every 6 months/ 1000 hours		
use Normal		CLIMATE Cold
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every 6 mg	onths/ 1000 hours	ı



HYDRAULIC SYSTEM Capacity: 40 liter (Hydraulic tank)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
Check every 10 hours, change every 2000) hours/ 12 months	
USE		CLIMATE
Biodegradable oil		Moderate
PRODUCT RECOMMENDATION 1		
Perlus Biosynth 46		
HYDRAULIC BRAKE SYSTEM Capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		
COOLING SYSTEM Capacity: 23,6 liter, Capacity: 25,5 liter (+	heater)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Check every 10 hours, change every 36 months/ 6000 hours