

# CATERPILLAR BACKHOE LOADERS 444E

## (2004-2011)

**ENGINE**

Capacity: 7,3 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
|-------------------------------|-------------------------------|-------------------------------|
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Change every 500 hours/ 3 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      |
|-----------------------------|-------------------------------|
| <b>Synfleet SHPD 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |

*Change every 500 hours/ 3 months***DIFFERENTIAL FRONT**

Capacity: 11 liter, Capacity: 14 liter (+ equal sized tires)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Gear Oil Alcat 50</b> |  |  |

*Change every 1000 hours*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |  |
|--------------------------|--|--|
| <b>Gear Oil Alcat 30</b> |  |  |

*Change every 1000 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gear Oil Alcat 10W</b> |  |  |

*Change every 1000 hours***DIFFERENTIAL REAR**

Capacity: 16-16,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

# CATERPILLAR BACKHOE LOADERS 444E

## (2004-2011)

**FINAL DRIVES FRONT**

Capacity: 0,7 liter (each side)

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Gear Oil Alcat 50</b> |  |               |

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Gear Oil Alcat 30</b> |  |          |

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Cold    |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Gear Oil Alcat 10W</b> |  |         |

**FINAL DRIVES REAR**

Capacity: 1,6 liter (each side)

| USE                          |                                     | CLIMATE       |
|------------------------------|-------------------------------------|---------------|
| Normal                       |                                     | Mediterranean |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2            |               |
| <b>Gearlube GL-5 85W-140</b> | <b>Unigear LS GL-3/GL-5 85W-140</b> |               |

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

# CATERPILLAR BACKHOE LOADERS 444E

## (2004-2011)

**TRANSMISSION**

Capacity: 18,5 liter

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |               |

*Change every 1000 hours*

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Cold    |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Gear Oil Alcat 10W</b> |  |         |

*Change every 1000 hours***TRANSMISSION Powershift**

Capacity: 19 liter

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |               |

*Change every 1000 hours*

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Cold    |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Gear Oil Alcat 10W</b> |  |         |

*Change every 1000 hours***HYDRAULIC SYSTEM**

Capacity: 40 liter

| USE                      |  | CLIMATE       |
|--------------------------|--|---------------|
| Normal                   |  | Mediterranean |
| PRODUCT RECOMMENDATION 1 |  |               |
| <b>Gear Oil Alcat 30</b> |  |               |

*Change every 2000 hours*

| USE                       |                           | CLIMATE  |
|---------------------------|---------------------------|----------|
| Normal                    |                           | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2  |          |
| <b>Gear Oil Alcat 10W</b> | <b>Perlus Biosynth 46</b> |          |

*Change every 2000 hours*

# CATERPILLAR BACKHOE LOADERS 444E

## (2004-2011)



### HYDRAULIC BRAKE SYSTEM

Capacity: 0,7 liter

| USE                       |  | CLIMATE  |
|---------------------------|--|----------|
| Normal                    |  | Moderate |
| PRODUCT RECOMMENDATION 1  |  |          |
| <b>Gear Oil Alcat 10W</b> |  |          |

### GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

### COOLING SYSTEM

Capacity: 23,1-25,3 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 17</b>     |  |          |

*Change every 6000 hours/ 72 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*