

CATERPILLAR FELLER BUNCHERS 2391



ENGINE C9 Acert
Capacity: 39 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |

Check every 10 hours, change every 1 months/ 250 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|-------------------------------|--|
| Agrisynth LSP 10W-40 | Multifleet SHPD 10W-40 | |

Check every 10 hours, change every 1 months/ 250 hours

| USE | CLIMATE |
|--------------------------|---------------|
| Alternative (acceptable) | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|-------------------------------|--|
| Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 | |

Check every 10 hours, change every 1 months/ 250 hours

| USE | CLIMATE |
|--------------------------|----------|
| Alternative (acceptable) | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|-------------------------------|-------------------------------|
| Synfleet SHPD 10W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 10W-40 |

Check every 10 hours, change every 1 months/ 250 hours

HYDRAULIC HOOD TILT SYSTEM
Capacity: 6,5 liter (Hydraulic tank)

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Gear Oil Alcat 30 | | |

Check every 10 hours

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|--------------------------|-----------------------------|
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

Check every 10 hours

CATERPILLAR FELLER BUNCHERS 2391

**HYDRAULIC SYSTEM**

Capacity: 262 liter (Hydraulic tank), Capacity: 454 liter (System)

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

Check every 10 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|-------------------------------|--------------------------|-----------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |

*Check every 10 hours, change every 6 months/ 1000 hours***HYDRAULIC SYSTEM VARIABLE PITCH FLEXXAIRE FAN**

Capacity: 0,65-1,22 liter

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 50 | | |

Check every 1000 hours, change every 48 months/ 6000 hours

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |

*Check every 1000 hours, change every 48 months/ 6000 hours***COOLING SYSTEM**

Capacity: 61 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 17 | | |

Check every 10 hours, change every 72 months/ 12000 hours

CATERPILLAR FELLER BUNCHERS 2391

**SWING REDUCTION UNIT**

Capacity: 10 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Change every 250 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Change every 250 hours

TRAVEL REDUCTION UNIT

Capacity: 9 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gear Oil Alcat 30 | Gear Oil Alcat 50 | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |

Check every 1 months/ 250 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.