## **CATERPILLAR PIPELAYERS 594H 96V**



| <b>ENGINE</b> Caterpillar D353 Capacity: 42,6 liter |                          |                          |
|---|--------------------------|--------------------------|
| USE   |                          | CLIMATE                  |
| Normal  |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40                              | Synfleet SHPD 10W-40     | Dieselfleet CD+ 15W-40   |
|   |                          |                          |

Change every 250 hours

| CABLE DRUM TRANSMISSION  |                          |               |
|--------------------------|--------------------------|---------------|
| USE                      |                          | CLIMATE       |
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| Gear Oil Alcat 30        | Gear Oil Alcat 50        |               |
| USE                      |                          | CLIMATE       |
| Normal                   |                          | Cold          |
| PRODUCT RECOMMENDATION 1 |                          |               |
| Gear Oil Alcat 10W       |                          |               |

| FINAL DRIVES<br>Capacity: 42,6 liter (each) |                          |          |
|---|--------------------------|----------|
| USE   |                          | CLIMATE  |
| Normal                                      |                          | Moderate |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2 |          |
| Gear Oil Alcat 30                           | Gear Oil Alcat 50        |          |
|   |                          | <u> </u> |

Check every 500 hours, change every 2000 hours

| USE  |  | CLIMATE |
|--|--|---------|
| Normal   |  | Arctic  |
| PRODUCT RECOMMENDATION 1                       |  |         |
| Gear Oil Alcat 10W                             |  |         |
| Chack ayang E00 bayra, abanga ayang 2000 bayra |  |         |

Check every 500 hours, change every 2000 hours

## **CATERPILLAR PIPELAYERS 594H 96V**



| TRANSMISSION Powershift Capacity: 129 liter    |                          |               |
|--|--------------------------|---------------|
| USE  |                          | CLIMATE       |
| Normal   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1                       | PRODUCT RECOMMENDATION 2 |               |
| Gear Oil Alcat 30                              | Gear Oil Alcat 50        |               |
| Check every 500 hours, change every 100        | 00 hours                 |               |
| USE  |                          | CLIMATE       |
| Normal   |                          | Cold          |
| PRODUCT RECOMMENDATION 1                       |                          |               |
| Gear Oil Alcat 10W                             |                          |               |
| Check every 500 hours, change every 1000 hours |                          |               |

| HYDRAULIC SYSTEM                   |                          |                          |
|------------------------------------|--------------------------|--------------------------|
| USE                                |                          | CLIMATE                  |
| Normal                             |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1           | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40             | Kroontrak MTH 10W-30     | Synfleet SHPD 10W-40     |
| Check every 500 hours, change ever | y 2000 hours             | 1                        |

| GREASE POINTS/NIPPLES    |  |          |
|--------------------------|--|----------|
| USE                      |  | CLIMATE  |
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| MoS2 Grease EP 2         |  |          |

| use<br>Normal            |                   | сымате<br>Mediterranean |
|--------------------------|-------------------|-------------------------|
|                          |                   |                         |
| Gear Oil Alcat 30        | Gear Oil Alcat 50 |                         |
| USE                      |                   | CLIMATE                 |
| Normal                   |                   | Cold                    |
| PRODUCT RECOMMENDATION 1 |                   |                         |
| Gear Oil Alcat 10W       |                   |                         |

## **CATERPILLAR PIPELAYERS 594H 96V**



| FLYWHEEL CLUTCH          |                          |               |
|--------------------------|--------------------------|---------------|
| USE                      |                          | CLIMATE       |
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| Gear Oil Alcat 30        | Gear Oil Alcat 50        |               |
| USE                      |                          | CLIMATE       |
| Normal                   |                          | Cold          |
| PRODUCT RECOMMENDATION 1 |                          |               |
| Gear Oil Alcat 10W       |                          |               |
| STEERING CLUTCHES USE    |                          | CLIMATE       |
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| Gear Oil Alcat 30        | Gear Oil Alcat 50        |               |
| USE                      |                          | CLIMATE       |
| Normal                   |                          | Cold          |
| PRODUCT RECOMMENDATION 1 |                          |               |
| Gear Oil Alcat 10W       |                          |               |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.