

# CATERPILLAR LOAD HAUL DUMPERS

## R1600G 9PP (2003-2008)

**ENGINE 3176C ATAAC**

Capacity: 36,1 liter

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

## PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40***Check every 10 hours, change every 1 months/ 250 hours*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Synfleet SHPD 10W-40**

## PRODUCT RECOMMENDATION 2

**Dieselfleet CD+ 15W-40**

## PRODUCT RECOMMENDATION 3

**Multifleet SHPD 10W-40***Check every 10 hours, change every 1 months/ 250 hours***DIFFERENTIAL FRONT**

Capacity: 70 liter (+ hub reductions)

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours***DIFFERENTIAL FRONT + AXLE OIL COOLING**

Capacity: 80 liter

USE	CLIMATE
Normal	Mediterranean

## PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

## PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

# CATERPILLAR LOAD HAUL DUMPERS

## R1600G 9PP (2003-2008)



### DIFFERENTIAL REAR

Capacity: 70 liter (+ hub reductions)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

### DIFFERENTIAL REAR + AXLE OIL COOLING

Capacity: 80 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

### HUB REDUCTIONS FRONT

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

# CATERPILLAR LOAD HAUL DUMPERS

## R1600G 9PP (2003-2008)



### HUB REDUCTIONS REAR

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

### TRANSMISSION Powershift

Capacity: 47 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30**

PRODUCT RECOMMENDATION 2

**Gear Oil Alcat 50***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 10W***Check every 1 months/ 250 hours, change every 6 months/ 1000 hours*

# CATERPILLAR LOAD HAUL DUMPERS

## R1600G 9PP (2003-2008)



### HYDRAULIC SYSTEM

Capacity: 125 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Gear Oil Alcat 30***Check every 10 hours, change every 2000 hours/ 12 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3

**Agrifluid HT***Check every 10 hours, change every 2000 hours/ 12 months*

USE	CLIMATE
Biodegradable oil	Moderate

PRODUCT RECOMMENDATION 1

**Perlus Biosynth 46***Check every 10 hours, change every 2000 hours/ 12 months*

### GREASE POINTS/NIPPLES

We are unable to give a standard recommendation for this component. Please contact our service department.

### COOLING SYSTEM

Capacity: 53 liter

USE	CLIMATE
Preferred, extended	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 17***Check every 10 hours, change every 48 months/ 6000 hours*

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12**

PRODUCT RECOMMENDATION 3

**Coolant -38 Organic NF***Check every 10 hours, change every 24 months/ 3000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.