DOOSAN (DAEWOO) FORKLIFT TRUCKS, DIESEL D/GXD D100 DHIM DE08TS (2004-



2007)

ENGINE Doosan DE08TS Capacity: 23,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agrisynth MSP 10W-40	Armado Synth 10W-40

Check every 10 hours, change every 1 months/ 250 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP 10W-40	Agrisynth MSP 10W-40	Armado Synth 10W-40

Change every 50 hours/ 1 week

DIFFERENTIAL Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
0/ 0000/ //0		

Change every 2000 hours/ 12 months

HUB REDUCTIONS Capacity: 4,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		
01	,		

Change every 2000 hours/ 12 months

TRANSMISSION Powershift Capacity: 28,4 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		
Change every 500 hours/ 3 months		

PRODUCT RECOMMENDATION

DOOSAN (DAEWOO) FORKLIFT TRUCKS, DIESEL D/GXD D100 DHIM DE08TS (2004-2007)



2007)

HYDRAULIC SYSTEM POWER STEER Capacity: 170 liter	ING	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus H 68	
Change every 2000 hours/ 12 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 32	Perlus H 22	
Change every 2000 hours/ 12 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.