

JCB WHEELED LOADERS 412E



ENGINE 1000

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Change every 250 hours/ 1 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Change every 100 hours

DIFFERENTIAL

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Change every 1000 hours/ 6 months

TRANSMISSION

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	ATF Dexron II-D	

Change every 500 hours/ 3 months

HYDRAULIC SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 32		

Change every 30 months/ 2400 hours

JCB WHEELED LOADERS 412E**HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 15		

Change every 1000 hours/ 6 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
HT Q9 High Grade Grease		

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.