

JCB TRACKED EXCAVATORS 820S (TILL 1999)

**ENGINE** Ford 2700

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|-------------------------------|--|
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Change every 250 hours/ 1 months

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-------------------------------|--|--|
| Multifleet SHPD 10W-40 | | |

Change every 250 hours/ 1 months

| USE | CLIMATE |
|--------|---------|
| Normal | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Multifleet SCD 10W | | |

Change every 250 hours/ 1 months

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|-------------------------------|--|
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Change every 100 hours

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-------------------------------|--|--|
| Multifleet SHPD 10W-40 | | |

Change every 100 hours

| USE | CLIMATE |
|-----------------|---------|
| Initial service | Arctic |

| PRODUCT RECOMMENDATION 1 | | |
|---------------------------|--|--|
| Multifleet SCD 10W | | |

Change every 100 hours

ENGINE Perkins 1000

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-------------------------------|-------------------------------|--|
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Change every 250 hours/ 1 months

JCB TRACKED EXCAVATORS 820S (TILL 1999)



| | | |
|---|---|--------------------------|
| USE Normal | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40 | | |
| <i>Change every 250 hours/ 1 months</i> | | |
| USE Normal | | CLIMATE Arctic |
| PRODUCT RECOMMENDATION 1 Multifleet SCD 10W | | |
| <i>Change every 250 hours/ 1 months</i> | | |
| USE Initial service | | CLIMATE Mediterranean |
| PRODUCT RECOMMENDATION 1 Dieselfleet CD+ 15W-40 | PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40 | |
| <i>Change every 100 hours</i> | | |
| USE Initial service | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40 | | |
| <i>Change every 100 hours</i> | | |
| USE Initial service | | CLIMATE Arctic |
| PRODUCT RECOMMENDATION 1 Multifleet SCD 10W | | |
| <i>Change every 100 hours</i> | | |
| ENGINE Perkins 4.248, 6.354 | | |
| USE Normal | | CLIMATE Mediterranean |
| PRODUCT RECOMMENDATION 1 Dieselfleet CD+ 15W-40 | PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40 | |
| <i>Change every 250 hours/ 1 months</i> | | |
| USE Normal | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40 | | |
| <i>Change every 250 hours/ 1 months</i> | | |

JCB TRACKED EXCAVATORS 820S (TILL 1999)



| | | |
|---|---|--------------------------|
| USE Normal | | CLIMATE Arctic |
| PRODUCT RECOMMENDATION 1 Multifleet SCD 10W | | |
| <i>Change every 250 hours/ 1 months</i> | | |
| USE Initial service | | CLIMATE Mediterranean |
| PRODUCT RECOMMENDATION 1 Dieselfleet CD+ 15W-40 | PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40 | |
| <i>Change every 100 hours</i> | | |
| USE Initial service | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40 | | |
| <i>Change every 100 hours</i> | | |
| USE Initial service | | CLIMATE Arctic |
| PRODUCT RECOMMENDATION 1 Multifleet SCD 10W | | |
| <i>Change every 100 hours</i> | | |
| ENGINE Perkins T4.236, T6.354 | | |
| USE Normal | | CLIMATE Mediterranean |
| PRODUCT RECOMMENDATION 1 Dieselfleet CD+ 15W-40 | PRODUCT RECOMMENDATION 2 Multifleet SHPD 15W-40 | |
| <i>Change every 250 hours/ 1 months</i> | | |
| USE Normal | | CLIMATE Moderate |
| PRODUCT RECOMMENDATION 1 Multifleet SHPD 10W-40 | | |
| <i>Change every 250 hours/ 1 months</i> | | |
| USE Normal | | CLIMATE Arctic |
| PRODUCT RECOMMENDATION 1 Multifleet SCD 10W | | |
| <i>Change every 250 hours/ 1 months</i> | | |

JCB TRACKED EXCAVATORS 820S (TILL 1999)



| USE | | CLIMATE |
|-------------------------------|-------------------------------|---------------|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 | |

Change every 100 hours

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SHPD 10W-40 | | |

Change every 100 hours

| USE | | CLIMATE |
|---------------------------|--|---------|
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SCD 10W | | |

Change every 100 hours

HYDRAULIC SYSTEM

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 32 | | |

Change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|--|---------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| MoS2 Grease EP 2 | | |

JCB TRACKED EXCAVATORS 820S (TILL 1999)



SWING REDUCTION UNIT

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 2000 hours

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 100 hours

SWING RING BEARINGS

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|---------------------------------|------------------------------|
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

SWING RING GEAR TEETH

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Compound OGL | | |

TRACK IDLER WHEELS

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Multifleet SCD 30 | | |

TRACK ROLLERS

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Multifleet SCD 30 | | |

JCB TRACKED EXCAVATORS 820S (TILL 1999)



TRAVEL REDUCTION UNIT

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 2000 hours

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Change every 100 hours

UNIVERSAL JOINTS + DRIVE SHAFTS

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| MoS2 Grease EP 2 | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.