

JCB SKID STEER LOADERS ROBOT 190

JCB 444 TIER 3 (2008 AND AFTER)



ENGINE JCB 444
Capacity: 10,8 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Change every 500 hours

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40

Change every 500 hours

USE
Severe

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Dieselfleet CD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Change every 250 hours

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40

Change every 250 hours

HYDRAULIC SYSTEM
Capacity: 35 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Synfleet SHPD 10W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40

Change every 2000 hours/ 24 months

GREASE POINTS/NIPPLES

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
HT Q9 High Grade Grease

PRODUCT RECOMMENDATION 2
Labora Grease

PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2

JCB SKID STEER LOADERS ROBOT 190

JCB 444 TIER 3 (2008 AND AFTER)

**COOLING SYSTEM**

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

CHAIN CASE

Capacity: 10,8 liter (Left), Capacity: 12,5 liter (Right)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Change every 2000 hours/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Synfleet SHPD 10W-40	Multifleet SHPD 10W-40	

Change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.