PRODUCT RECOMMENDATION

# KUBOTA UTILITY VEHICLES RTV RTV-X1120D KUBOTA D1105 (2013 AND AFTER)

**ENGINE** Kubota D1105
Capacity: 4,1 liter, Filter capacity: 0,3 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 30** | | |

*Check every 10 hours, change every 200 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agridiesel CRD+ 15W-40** | **Multifleet SHPD 15W-40** | **Multifleet SCD 20W-20** |

*Check every 10 hours, change every 200 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Kroontrak MTH 10W-30** | | |

*Check every 10 hours, change every 200 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 10W** | | |

*Check every 10 hours, change every 200 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal, low sulphur fuel | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 30** | | |

*Check every 10 hours, change every 200 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal, low sulphur fuel | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 20W-20** | | |

*Check every 10 hours, change every 200 hours*

| USE | | CLIMATE |
|---|---|---|
| Normal, low sulphur fuel | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Kroontrak CVT 10W-40** | **Kroontrak MTH 10W-30** | **Synfleet SHPD 10W-40** |

*Check every 10 hours, change every 200 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# KUBOTA UTILITY VEHICLES RTV RTV-X1120D KUBOTA D1105 (2013 AND AFTER)

| USE | | CLIMATE |
|---|---|---|
| Normal, low sulphur fuel | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 10W** | | |

*Check every 10 hours, change every 200 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 30** | | |

*Change every 50 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Agridiesel CRD+ 15W-40** | **Multifleet SHPD 15W-40** | **Multifleet SCD 20W-20** |

*Change every 50 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Kroontrak MTH 10W-30** | | |

*Change every 50 hours*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| **Multifleet SCD 10W** | | |

*Change every 50 hours*

**DIFFERENTIAL FRONT** (4x4)
Capacity: 0,6 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |

*Change every 400 hours*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# KUBOTA UTILITY VEHICLES RTV RTV-X1120D KUBOTA D1105 (2013 AND AFTER)

## KNUCKLE CASE FRONT (4x4)
Capacity: 0,25 liter (each)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |
| *Change every 400 hours* | | |

## TRANSMISSION CONTINUOUSLY VARIABLE HYDROSTATIC VHT
Capacity: 7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |
| *Change every 400 hours* | | |

## HYDRAULIC SYSTEM
Capacity: 18 liter (Hydraulic tank)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Agrifluid HT** | | |
| *Change every 200 hours* | | |

## HYDRAULIC BRAKE SYSTEM
Capacity: 0,4 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Drauliquid DOT 3** | | |
| *Change every 24 months* | | |

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Labora Grease** | **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# KUBOTA UTILITY VEHICLES RTV RTV-X1120D KUBOTA D1105 (2013 AND AFTER)

**COOLING SYSTEM**
Capacity: 6,1 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Coolant -38 Organic NF** | **Coolant -26** | |
| *Change every 24 months* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367