MANITOU FORKLIFT TRUCKS S-TC S404TC-D FORD 192 CI



ENGINE Ford 192 CI Capacity: 6,65 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 150 hours

DIFFERENTIAL FRONT Capacity: 45,9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus
Change every 1200 hours		,

DIFFERENTIAL REAR Capacity: 5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus
Change every 1200 hours		·

HUB REDUCTIONS REAR Capacity: 1,1 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Agrifluid HT-Plus
Change every 1200 hours		<u> </u>

TRANSMISSION POWERSHIFT 4/4 Capacity: 18 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF-A		
Check every 150 hours, change every 600) hours	

MANITOU FORKLIFT TRUCKS S-TC S404TC-D FORD 192 CI



HYDRAULIC SYSTEM Capacity: 67,8 liter (Hydraulic tank)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
	!

Check every 10 hours, change every 600 hours

ENDATION 3

GREASE POINTS/NIPPLES GENERAL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM Capacity: 10,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours		

MAST CHAINS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40		
	2001		

Check every 10 hours, change every 300 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.