MANITOU MANISCOPIC MLT MLT 735-120 MERCEDES OM904LA (2012 AND AFTER)



ENGINE Mercedes-Benz OM904LA Capacity: 16 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth MSP 10W-40	Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 8 hours, change every 6 months/ 500 hours

ANGLE GEARBOX Capacity: 2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 1000 hours/ 12 mont.	hs	

DIFFERENTIAL FRONT Capacity: 8,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 6 months/ 500 hours	·

DIFFERENTIAL REAR Capacity: 8,1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 6 months/ 500 hours	

HUB REDUCTIONS FRONT Capacity: 0,8 liter (each)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Change every 6 months/ 500 hours		

MANITOU MANISCOPIC MLT MLT 735-120 MERCEDES OM904LA (2012 AND AFTER)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Unigear HS GL-3/GL-5 80W-90	

Change every 6 months/ 500 hours

TRANSMISSION HYDROSTATIC Capacity: 16,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Almirol	
Change every 1000 hours/ 12 months	

HYDRAULIC SYSTEM Capacity: 135 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 1000 hours/ 12 months	

COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.