

MANITOU MANISCOPIC MRT MRT 2150 PRIVILEGE E3 MERCEDES-BENZ OM904LA (413080 ->)



ENGINE Mercedes-Benz OM904LA
Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 500 hours/ 12 months

DIFFERENTIAL FRONT
Capacity: 11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 250 hours, change every 1000 hours/ 12 months

DIFFERENTIAL REAR
Capacity: 11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT
Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS REAR
Capacity: 1,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 250 hours, change every 1000 hours/ 12 months

MANITOU MANISCOPIC MRT MRT 2150 PRIVILEGE E3 MERCEDES-BENZ OM904LA (413080 ->)

**REDUCTION UNIT FRONT 2/2**

Capacity: 2,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 250 hours, change every 1000 hours/ 12 months

HYDRAULIC SYSTEM HYDROSTATIC DRIVE

Capacity: 210 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46

Check every 50 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM

Capacity: 18 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF

Check every 10 hours, change every 1500 hours

SWING REDUCTION UNIT

Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Abacot MEP HD 150

PRODUCT RECOMMENDATION 2

Abacot MEP 150

Check every 250 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

**MANITOU MANISCOPIC MRT MRT 2150
PRIVILEGE E3 MERCEDES-BENZ OM904LA
(413080 ->)**



information contained herein is subject to changes without notification.