

MASSEY FERGUSON 4300 MF 4355 (2001-2004)



ENGINE Perkins 1004.40T
Capacity: 6,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP Ultra 10W-40

PRODUCT RECOMMENDATION 2

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 3

Kroontrak CVT 10W-40

Check every 10 hours, change every 300 hours

DIFFERENTIAL FRONT AG 105
Capacity: 7,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 300 hours, change every 1200 hours

DIFFERENTIAL FRONT AG 66
Capacity: 5,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 300 hours, change every 1200 hours

DIFFERENTIAL FRONT AG 75/85
Capacity: 5,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 300 hours, change every 1200 hours

HUB REDUCTIONS FRONT AG 105
Capacity: 1,2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 300 hours, change every 1200 hours

MASSEY FERGUSON 4300 MF 4355 (2001-2004)



HUB REDUCTIONS FRONT AG 66

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 300 hours, change every 1200 hours*

HUB REDUCTIONS FRONT AG 75/85

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 300 hours, change every 1200 hours*

HUB REDUCTIONS REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

POWER TAKE OFF FRONT

Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90*Check every 100 hours, change every 1200 hours*

TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 50 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40*Check every 100 hours, change every 1200 hours*

MASSEY FERGUSON 4300 MF 4355 (2001-2004)**HYDRAULIC BRAKE SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 300 hours, change every 2400 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 100 hours

COOLING SYSTEM

Capacity: 17,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.