

# MASSEY FERGUSON 5600 MF 5609 DYNA-4

## (2013-2018)



**ENGINE** Sisu 33DT  
Capacity: 13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth LSP 10W-40</b>	<b>Armado Synth LSP Ultra 10W-40</b>

*Check every 10 hours, change every 500 hours/ 12 months*

**DIFFERENTIAL FRONT** Dana  
Capacity: 5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 12 months/ 200 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 100 hours*

**HUB REDUCTIONS FRONT** Dana  
Capacity: 0,8 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 12 months/ 200 hours, change every 12 months/ 1000 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Change every 100 hours*

# MASSEY FERGUSON 5600 MF 5609 DYNA-4

## (2013-2018)



### POWER TAKE OFF FRONT

Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Kroontrak MTH 10W-30</b>

*Check every 10 hours, change every 500 hours/ 12 months*

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Kroontrak MTH 10W-30</b>

*Change every 50 hours*

### TRANSAXLE Dyna-4

Capacity: 65-75 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak CVT 10W-40</b>	<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>

*Check every 10 hours, change every 1500 hours/ 24 months*

### GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
<b>Multi Purpose Grease 3</b>		

*Change every 50 hours*

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours*

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
<b>Gear Grease EP 1</b>		

*Change every 50 hours*

# MASSEY FERGUSON 5600 MF 5609 DYNA-4 (2013-2018)

**COOLING SYSTEM**

Capacity: 13,6 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12****PRODUCT RECOMMENDATION 3****Coolant -38 Organic NF***Check every 10 hours, change every 1500 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*