MASSEY FERGUSON 6100 MF 6160 (1995-1999)



ENGINE Perkins 1006.6HR4 Capacity: 14,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Kroontrak CVT 10W-40

Change every 250 hours/ 6 months

DIFFERENTIAL FRONT (4x4) Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
0		

Check every 250 hours, change every 1000 hours/12 months

HUB REDUCTIONS FRONT (4x4) Capacity: 1,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	
Check every 250 hours, change eve	ery 1000 hours/ 12 months	

TRANSAXLE/HYDRAULIC SYSTEM 32/32 Capacity: 62 liter		
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Kroontrak CVT 10W-40		

Check every 100 hours, change every 1000 hours/ 12 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 10 hours	,	,

MASSEY FERGUSON 6100 MF 6160 (1995-1999)



COOLING SYSTEM Capacity: 25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 100 hours, change eve	ry 1000 hours/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.