

MASSEY FERGUSON 6200 MF 6235 I (1998-2000)



ENGINE Perkins 1004.40T
Capacity: 7,4 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------------|-----------------------------|-----------------------------|
| Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40 | Kroontrak CVT 10W-40 |

Change every 300 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 5,8 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 300 hours, change every 900 hours/ 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 0,9 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 300 hours, change every 900 hours/ 12 months

TRANSAXLE/HYDRAULIC SYSTEM 16/16
Capacity: 62 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|-----------------------------|--|--|
| Kroontrak CVT 10W-40 | | |

Check every 100 hours, change every 900 hours/ 12 months

MASSEY FERGUSON 6200 MF 6235 I (1998-2000)



GREASE POINTS/NIPPLES

| USE | CLIMATE |
|--------|----------|
| Normal | Tropical |

PRODUCT RECOMMENDATION 1

Multi Purpose Grease 3*Check every 50 hours*

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 50 hours*

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

PRODUCT RECOMMENDATION 1

Gear Grease EP 1*Check every 50 hours*

COOLING SYSTEM

Capacity: 16,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Change every 900 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.