

MASSEY FERGUSON 6400 DYNA 6465

DYNA-6/DYNASHIFT TIER III (2007-2013)



ENGINE Perkins 1106D-E66TA
Capacity: 14,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 400 hours

DIFFERENTIAL FRONT Carraro
Capacity: 8,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 400 hours, change every 800 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 50 hours

DIFFERENTIAL FRONT Dana
Capacity: 9,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 400 hours, change every 800 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours

MASSEY FERGUSON 6400 DYNA 6465

DYNA-6/DYNASHIFT TIER III (2007-2013)


HUB REDUCTIONS FRONT Carraro

Capacity: 0,6 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 400 hours, change every 800 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Change every 50 hours
HUB REDUCTIONS FRONT Dana

Capacity: 0,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 400 hours, change every 800 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 50 hours
POWER TAKE OFF FRONT

Capacity: 2,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	

MASSEY FERGUSON 6400 DYNA 6465

DYNA-6/DYNASHIFT TIER III (2007-2013)



TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 69-71 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak CVT 10W-40		

Check every 10 hours, change every 1200 hours/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multi Purpose Grease 3		

Change every 50 hours

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

Change every 50 hours

COOLING SYSTEM

Capacity: 25,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 50 hours, change every 1200 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.