

MASSEY FERGUSON 7200 7254 (2000-2002)

ENGINE 634 DSBIEL
Capacity: 24 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Multifleet SCD 30	Multifleet SCD 20W-20

Check every 10 hours, change every 200 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Multifleet SHPD 15W-40	

Check every 10 hours, change every 200 hours/ 12 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	
Multifleet SCD 10W	

Check every 10 hours, change every 200 hours/ 12 months

FINAL REDUCTION FINAL DRIVE(S)
Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

Check every 100 hours, change every 500 hours/ 24 months

GEARBOX
Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Labora Grease	

Check every 100 hours

MASSEY FERGUSON 7200 7254 (2000-2002)**KNIFE DRIVE GEARBOX**

Capacity: 0,85 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 100 hours, change every 500 hours***TRANSMISSION HYDROSTATIC 3/3**

Capacity: 7,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 100 hours, change every 500 hours/ 24 months***HYDRAULIC SYSTEM**

Capacity: 90 liter

USE

Normal

CLIMATE

Tropical

PRODUCT RECOMMENDATION 1**Perlus AF 100***Check every 10 hours, change every 1000 hours/ 24 months***USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Perlus H 68****PRODUCT RECOMMENDATION 2****Perlus AF 68***Check every 10 hours, change every 1000 hours/ 24 months***GREASE POINTS/NIPPLES****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Check every 50 hours*

MASSEY FERGUSON 7200 7254 (2000-2002)**COOLING SYSTEM**

Capacity: 48 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.