MASSEY FERGUSON 7700 MF 7724 DYNA-VT (2015-2020)



ENGINE Agco Power 74 AWF Capacity: 25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40	Agridiesel MSP 15W-40

Check every 10 hours, change every 500 hours/ 12 months

Check every 200 hours, change every 1000 hours/12 months

HUB REDUCTIONS FRONT Capacity: 2-2,2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 200 hours, change every 1000 hours/12 months

HUB REDUCTIONS REAR Capacity: 19 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	
Check every 12 months/ 500 hours, change every 2000 hours/ 24 months		

POWER TAKE OFF FRONT Capacity: 3,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30
Check every 10 hours, change ever	y 500 hours/ 6 months	

TRANSAXLE Dyna-VT

MASSEY FERGUSON 7700 MF 7724 DYNA-VT (2015-2020)



Capacity: 64 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak CVT 10W-40		
Check every 10 hours, change every 2000) hours/ 24 months	
AUXILIARY HYDRAULIC SYSTEM Capacity: 100 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak CVT 10W-40		
Check every 10 hours, change every 1500) hours/24 months	
GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multi Purpose Grease 3		
Change every 50 hours		

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

KROON-OIL B.V. Postbus 149 7600 AC Almelo

USE

USE

Normal

Normal

PRODUCT RECOMMENDATION 1

Change every 50 hours

PRODUCT RECOMMENDATION 1

Gear Grease EP 1

Change every 50 hours

Labora Grease

CLIMATE

CLIMATE

Cold

Mediterranean

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2

MASSEY FERGUSON 7700 MF 7724 DYNA-VT (2015-2020)



COOLING SYSTEM Capacity: 28 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 10 hours, change every 1500 hours/24 months		

Check every 10 hours, change every 1500 hours/24 months

SELECTIVE CATALYTIC REDUCTION SYSTEM (SCR) Capacity: 40 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.