Check every 10 hours, change every 250 hours

Check every 1 months, change every 500 hours

## **MASSEY FERGUSON 8000 8560** (1986-1992)



<b>ENGINE</b> Cummins 6BTA5.9 Capacity: 16,2 liter, Filter capacity: 2 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SHPD 15W-40	Multifleet SHPD 20W-50	
Check every 10 hours, change every 250 kg	hours	
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	

HUB REDUCTIONS FRONT Capacity: 5,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Unigear HS GL-3/GL-5 80W-90	
Check every 1 months, change every 500 hours	

HUB REDUCTIONS REAR Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Unigear HS GL-3/GL-5 80W-90	

TRANSMISSION MANUAL 3/3 Capacity: 6,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Unigear HS GL-3/GL-5 80W-90	
Check every 1 months, change every 500 hours	,

## **MASSEY FERGUSON 8000 8560** (1986-1992)



HYDRAULIC SYSTEM Capacity: 90 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Change every 2000 hours	<u> </u>	

HYDRAULIC BRAKE SYSTEM Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multi Purpose Grease 3		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		

## **MASSEY FERGUSON 8000 8560** (1986-1992)



GREASE POINTS/NIPPLES WHEEL BEA	RINGS REAR	
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multi Purpose Grease 3		
Check every 50 hours, change every 500 h	nours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 50 hours, change every 500 h	hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Gear Grease EP 1		
Check every 50 hours, change every 500 h	nours	

COOLING SYSTEM Capacity: 36 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every	y 24 months	•

CHAINS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Multifleet SCD 30	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.