

MCCORMICK CX CX 100 (2001-2007)

ENGINE Perkins
Capacity: 7,3 liter

| USE | CLIMATE |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|-------------------------------|
| Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 | Multifleet SHPD 20W-50 |

Check every 10 hours, change every 250 hours/ 12 months

| USE | CLIMATE |
|--------|---------|
| Normal | Cold |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------|--------------------------|---------------------------|
| Kroontrak MTH 10W-30 | Asyntho 5W-30 | Armado Synth 5W-30 |

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT (4x4)
Capacity: 5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|------------------------------|-------------------------------------|--|
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 250 hours, change every 1000 hours

HUB REDUCTIONS FRONT (4x4)
Capacity: 0,6 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|------------------------------|-------------------------------------|--|
| Gearlube GL-5 85W-140 | Unigear LS GL-3/GL-5 85W-140 | |

Check every 250 hours, change every 1000 hours

POWER TAKE OFF
Capacity: 0,65 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|--------------------------|--|--|
| Agrifluid HT-Plus | | |

Check every 10 hours, change every 250 hours

MCCORMICK CX CX 100 (2001-2007)**TRANSAXLE/HYDRAULIC SYSTEM 16/8**

Capacity: 37 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |

Check every 10 hours, change every 1000 hours/ 24 months

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 50 hours

COOLING SYSTEM

Capacity: 17,5 liter

| USE | | CLIMATE |
|-------------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |

Check every 10 hours, change every 2000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.