## **MCCORMICK GM GM45 TIER2** (2004-2008)



<b>ENGINE</b> Yanmar 4TNV84 - KLAN Capacity: 5,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 250 hours

<b>DIFFERENTIAL FRONT</b> Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT
Check every 100 hours, change even	v 1000 hours/ 12 months	·

POWER TAKE OFF FRONT
Capacity: 0,35 liter

USE

Normal

PRODUCT RECOMMENDATION 1

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Agrifluid Synth XHP Ultra Kroontrak MTH 10W-30 Agrifluid HT

Check every 50 hours

TRANSAXLE/HYDRAULIC SYSTEM Capacity: 24 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT
Check every 100 hours, change every	y 1000 hours/ 12 months	·
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Kroontrak MTH 10W-30	Agrifluid HT
Change every 500 hours	,	

## **MCCORMICK GM GM45 TIER2** (2004-2008)



COOLING SYSTEM Capacity: 2,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Check every 10 hours, change every	/ 1000 hours/ 12 months	•

Check every 10 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.