

# MCCORMICK MC MC120 POWER 6 (2003-2007)



**ENGINE 6TWH**  
Capacity: 13,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 20W-50**

*Check every 10 hours, change every 500 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

*Check every 10 hours, change every 500 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Multifleet SHPD 10W-40**

*Check every 10 hours, change every 500 hours*

**DIFFERENTIAL FRONT MFD**  
Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140**

*Check every 250 hours, change every 500 hours*

**DIFFERENTIAL FRONT INDEPENDENT FRONT SUSPENSION**  
Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 85W-140**

PRODUCT RECOMMENDATION 2

**Unigear LS GL-3/GL-5 85W-140**

*Check every 250 hours, change every 500 hours*

# MCCORMICK MC MC120 POWER 6 (2003-2007)



## HUB REDUCTIONS FRONT Independent Front Suspension

Capacity: 1,5 liter, Capacity: 2 liter (+ front brakes)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

*Check every 250 hours, change every 500 hours*

## HUB REDUCTIONS FRONT MFD

Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

*Check every 250 hours, change every 500 hours*

## TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 75 liter, Capacity: 12 liter (extra capacity)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Agrifluid HT-Plus</b>		

*Check every 10 hours, change every 1000 hours*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Check every 50 hours*

## COOLING SYSTEM

Capacity: 28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Check every 10 hours, change every 2000 hours*

# MCCORMICK MC MC120 POWER 6 (2003-2007)



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*