ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR32E DEUTZ F4M-1008



(1995-2003)

ENGINE Deutz F4M-1008		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Armado Synth 10W-40	
Change every 250 hours/ 3 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrisynth LSP 10W-40	Armado Synth 10W-40	
Change every 50 hours		
DIFFERENTIAL		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 1500 hours/ 12 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		
Change every 500 hours		
TRANSMISSION		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Gearlube LS 80W-90

Change every 500 hours

Change every 1500 hours/ 12 months

USE

Initial service

PRODUCT RECOMMENDATION 1

CLIMATE

Moderate

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR32E DEUTZ F4M-1008



(1995-2003)

1	
HYDRAULIC SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 12 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 1500 hours	
HYDROSTATIC DRIVE	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 12 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 1500 hours	
GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

PRODUCT RECOMMENDATION

ATLAS WEYHAUSEN (WEYCOR) WHEELED LOADERS AR AR32E DEUTZ F4M-1008



(1995-2003)

BRAKE SYSTEM RESERVOIR	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 1500 hours/ 12 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 500 hours	
PLAIN BEARINGS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

ROLLING CONTACT BEARINGS	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.