

# AUSA WHEELED DUMPERS 150 DF DEUTZ-DITER LKS-R (1994-2004)



**ENGINE** Deutz-Diter LKS-R  
Capacity: 1,75 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|--------------------------|
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SCD 30</b> |

*Change every 150 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Cold    |

| PRODUCT RECOMMENDATION 1     |  |  |
|------------------------------|--|--|
| <b>Multifleet SCD 20W-20</b> |  |  |

*Change every 150 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3 |
|-------------------------------|-------------------------------|--------------------------|
| <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> | <b>Multifleet SCD 30</b> |

*Change every 50 hours*

| USE             | CLIMATE |
|-----------------|---------|
| Initial service | Cold    |

| PRODUCT RECOMMENDATION 1     |  |  |
|------------------------------|--|--|
| <b>Multifleet SCD 20W-20</b> |  |  |

*Change every 50 hours*

**TRANSMISSION DIFFERENTIAL**  
Capacity: 2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Change every 900 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Change every 50 hours*

# AUSA WHEELED DUMPERS 150 DF DEUTZ-DITER LKS-R (1994-2004)



## HYDRAULIC SYSTEM

Capacity: 16,5 liter (Hydraulic tank)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Perlus H 68***Change every 900 hours*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

**Perlus H 68***Change every 150 hours*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,25 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid-S DOT 4***Change every 1000 hours*

## ARTICULATION JOINTS

We are unable to give a standard recommendation for this component. Please contact our service department.

## GREASE POINTS/NIPPLES

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Change every 50 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.