

AUSA WHEELED DUMPERS 150 DF

PERKINS 103-07 (1994-2004)



ENGINE Perkins 103-07 (KL)
Capacity: 2,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30

Change every 150 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Change every 150 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30

Change every 50 hours

USE	CLIMATE
Initial service	Cold

PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Change every 50 hours

TRANSMISSION DIFFERENTIAL
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 900 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 50 hours

AUSA WHEELED DUMPERS 150 DF

PERKINS 103-07 (1994-2004)



HYDRAULIC SYSTEM

Capacity: 16,5 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 68*Change every 900 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 68*Change every 150 hours*

HYDRAULIC BRAKE SYSTEM

Capacity: 0,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-S DOT 4*Change every 1000 hours*

ARTICULATION JOINTS

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 50 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.