AUSA WHEELED DUMPERS 300 RMA DEUTZ-DITER D-303-2 (1996-2005)



ENGINE Deutz-Diter D303-2		
Capacity: 4,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30
Change every 250 hours/ 6 months		
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Change every 250 hours/ 6 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40	Multifleet SCD 30
Change every 50 hours		
USE		CLIMATE
use Initial service		climate Cold
Initial service PRODUCT RECOMMENDATION 1		
Initial service		
Initial service PRODUCT RECOMMENDATION 1		
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20		
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20		
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours TRANSMISSION DIFFERENTIAL		
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours TRANSMISSION DIFFERENTIAL Capacity: 2 liter		Cold
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours TRANSMISSION DIFFERENTIAL Capacity: 2 liter USE		Cold
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours TRANSMISSION DIFFERENTIAL Capacity: 2 liter USE Normal		Cold
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours TRANSMISSION DIFFERENTIAL Capacity: 2 liter USE Normal PRODUCT RECOMMENDATION 1		Cold
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours TRANSMISSION DIFFERENTIAL Capacity: 2 liter USE Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90		Cold
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours TRANSMISSION DIFFERENTIAL Capacity: 2 liter USE Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1000 hours		Cold CLIMATE Moderate
Initial service PRODUCT RECOMMENDATION 1 Multifleet SCD 20W-20 Change every 50 hours TRANSMISSION DIFFERENTIAL Capacity: 2 liter USE Normal PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90 Change every 1000 hours USE		CLIMATE Moderate CLIMATE

Change every 50 hours

AUSA WHEELED DUMPERS 300 RMA DEUTZ-DITER D-303-2 (1996-2005)



HYDRAULIC SYSTEM Capacity: 30 liter (Hydraulic tank)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 68	
Change every 1000 hours	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 68	
Change every 100 hours	

HYDRAULIC ACTUATION OIL IMMERSED BRAKES Capacity: 0,25 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
LHM +				
Change every 500 hours				

ARTICULATION JOINTS

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 50 hours	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.