## AUSA WHEELED DUMPERS D 700 AP KUBOTA V3300-T (2006 AND AFTER)



| SE                                |                          | CLIMATE                  |
|-----------------------------------|--------------------------|--------------------------|
| Normal                            |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Dieselfleet CD+ 15W-40            | Multifleet SHPD 15W-40   | Multifleet SHPD 20W-50   |
| Change every 250 hours/ 12 months | 3                        |                          |
| USE                               |                          | CLIMATE                  |
| Normal                            |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40              | Kroontrak MTH 10W-30     | Synfleet SHPD 10W-40     |
| Change every 250 hours/ 12 months | 3                        |                          |
| USE                               |                          | CLIMATE                  |
| Initial service                   |                          | Mediterranean            |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Dieselfleet CD+ 15W-40            | Multifleet SHPD 15W-40   | Multifleet SHPD 20W-50   |
| Change every 50 hours             |                          |                          |
| USE                               |                          | CLIMATE                  |
| Initial service                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40              | Kroontrak MTH 10W-30     | Synfleet SHPD 10W-40     |
| Change every 50 hours             | <u> </u>                 | '                        |

| DIFFERENTIAL FRONT Capacity: 11,37 liter             |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                             |          |
| Agrifluid HT   |          |
| Check every 40 hours, change every 12 months/ 750 ho | purs     |

| <b>DIFFERENTIAL REAR</b> Capacity: 11,37 liter |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                       |          |
| Agrifluid HT                                   |          |
| Check every 40 hours, change every 12 r        | ) hours  |

Change every 50 hours

## AUSA WHEELED DUMPERS D 700 AP KUBOTA V3300-T (2006 AND AFTER)



| POWERSHUTTLE AND CONVERTER 4/4 Capacity: 11,95 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                             | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30                                 | Multifleet SCD 10W       | ATF Dexron II-D          |
| Check every 40 hours, change every                   | y 750 hours              |                          |
| USE  |                          | CLIMATE                  |
| Initial service                                      |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                             | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak MTH 10W-30                                 | Multifleet SCD 10W       | ATF Dexron II-D          |

| TRANSFERBOX<br>Capacity: 1,45 liter |                             |          |
|-------------------------------------|-----------------------------|----------|
| USE                                 |                             | CLIMATE  |
| Normal                              |                             | Moderate |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                | Unigear HS GL-3/GL-5 80W-90 |          |
| 0/ / / /                            | 10 11 /750 /                |          |

Check every 40 hours, change every 12 months/750 hours

| USE                              |                          | CLIMATE  |
|----------------------------------|--------------------------|----------|
| Normal                           |                          | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 |          |
| Perlus H 46                      | Perlus AF 46             |          |
| Check every 40 hours, change eve | ry 1000 hours            |          |
| USE                              |                          | CLIMATE  |
| Initial service                  |                          | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2 |          |
| Perlus H 46                      | Perlus AF 46             |          |

## **AUSA WHEELED DUMPERS D 700 AP KUBOTA V3300-T** (2006 AND AFTER)



| HYDRAULIC BRAKE SYSTEM<br>Capacity: 0,95 liter |                          |                          |
|--|--------------------------|--------------------------|
| USE  |                          | CLIMATE                  |
| Normal   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1                       | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| LHM +  | Perlus H 32              | Perlus AF 32             |
| Check every 40 hours, change eve               | ry 750 hours             |                          |

## **GREASE POINTS/NIPPLES**

We are unable to give a standard recommendation for this component. Please contact our service department.

| COOLING SYSTEM Capacity: 9 liter             |          |
|--|----------|
| USE  | CLIMATE  |
| Normal                                       | Moderate |
| PRODUCT RECOMMENDATION 1                     |          |
| Coolant -38 Organic NF                       |          |
| Check every 40 hours, change every 24 months | ·        |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.