BARFORD SITE DUMPERS SX3000 DEUTZ (TILL 2007)



| ENGINE Deutz F2L-2011 | | |
|--------------------------|--------------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SHPD 20W-50 | | |
| Change every 100 hours | | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Multifleet SHPD 10W-40 | Multifleet SHPD 15W-40 | |
| Change every 100 hours | | |

| DIFFERENTIAL FRONT | |
|-----------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT-Plus | |
| Change every 800 hours/ 12 months | · |

| DIFFERENTIAL REAR | |
|-----------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT-Plus | |
| Change every 800 hours/ 12 months | |

| GEARBOX Newage | | |
|-----------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change every 800 hours/ 12 months | 3 | 1 |

BARFORD SITE DUMPERS SX3000 DEUTZ (TILL 2007)



| HUB REDUCTIONS FRONT | | |
|-----------------------------------|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT-Plus | | |
| Change every 800 hours/ 12 months | | |

| HUB REDUCTIONS REAR | |
|---------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT-Plus | |
| Change average 200 have / 40 magnific | · |

Change every 800 hours/ 12 months

| TRANSFERBOX Newage | | |
|---------------------------------|-----------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |
| Change avery 200 hours/12 month | | |

Change every 800 hours/ 12 months

| HYDRAULIC SYSTEM | | |
|------------------------------------|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 32 | | |
| Change every 1200 hours/ 12 months | | |

| HYDRAULIC BRAKE SYSTEM | | |
|--------------------------|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus H 32 | | |

BARFORD SITE DUMPERS SX3000 DEUTZ (TILL 2007)



| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.