

BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T17C (6X6) ADE 366TI



ENGINE ADE/Mercedes-Benz 366TI
Capacity: 20 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Change every 250 hours/ 6 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Synfleet SHPD 10W-40	Armado Synth 5W-30

Change every 100 hours

DRIVE AXLES Bell
Capacity: 40 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Check every 250 hours, change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 250 hours, change every 2000 hours

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Change every 100 hours

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Change every 100 hours

BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T17C (6X6) ADE 366TI

**FINAL DRIVES**

Capacity: 2 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Check every 250 hours, change every 2000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 250 hours, change every 2000 hours*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Change every 100 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Change every 100 hours***TRANSFERBOX Bell**

Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 1000 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 100 hours*

BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T17C (6X6) ADE 366TI



TRANSMISSION Allison MD3560P 6/1
Capacity: 28 liter (Dry fill), Capacity: 18 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 1000 hours

HYDRAULIC SYSTEM
Capacity: 80 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	Perlus H 32

Change every 2000 hours

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Perlus H 46	Perlus H 68	Perlus AF 46

Change every 2000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Matic 2032	ATF Almirol	Perlus H 32

Change every 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HT Q9 High Grade Grease	Labora Grease	

BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T17C (6X6) ADE 366TI

**COOLING SYSTEM**

Capacity: 47 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.