PRODUCT RECOMMENDATION

BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T25 (6X4) DEUTZ BF6L513RC

ENGINE Deutz BF6L-513R
Capacity: 22 liter, Filter capacity: 4 liter

USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		

Change every 250 hours/ 6 months

USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	**Multifleet SCD 30**

Change every 250 hours/ 6 months

USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**

Change every 250 hours/ 6 months

USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		

Change every 250 hours/ 6 months

USE		CLIMATE
Normal, fuel sulfur level <0,5 %		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Change every 250 hours/ 6 months

DIFFERENTIAL FRONT Bell
Capacity: 48 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T25 (6X4) DEUTZ BF6L513RC

DIFFERENTIAL MIDDLE Bell
Capacity: 48 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

FINAL DRIVES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

TRANSMISSION ZF 6WG200 6/3
Capacity: 28 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Dieselfleet CD+ 15W-40	**Multifleet SHPD 15W-40**	

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	**Synfleet SHPD 10W-40**	**Multifleet SHPD 10W-40**

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 20W-20	**HDX 20W-20**	

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SCD 10W	**HDX 10W**	**ATF Almirol**

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

BELL EQUIPMENT TIMBER TRUCKS / FORWARDERS T T25 (6X4) DEUTZ BF6L513RC

HYDRAULIC SYSTEM
Capacity: 162 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	**Perlus H 68**	

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367