

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25DN MK 7 (6X6) MERCEDES-BENZ OM926LA (STAGE



ENGINE Mercedes-Benz OM926LA
Capacity: 29 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth LSP 10W-40	Armado Synth 10W-40

Change every 500 hours

DIFFERENTIAL FRONT 14R8E
Capacity: 30 liter (Dry fill), Capacity: 29 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Check every 500 hours, change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 500 hours, change every 1000 hours

DIFFERENTIAL MIDDLE 14R8F
Capacity: 27 liter (Dry fill), Capacity: 26 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Unigear LS GL-3/GL-5 85W-140		

Check every 500 hours, change every 1000 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gearlube LS 80W-90		

Check every 500 hours, change every 1000 hours

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25DN MK 7 (6X6) MERCEDES-BENZ OM926LA (STAGE

**DIFFERENTIAL REAR 14R8E**

Capacity: 29 liter (Dry fill), Capacity: 28 liter (Service fill)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Check every 500 hours, change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 500 hours, change every 1000 hours***FINAL DRIVES**

Capacity: 4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Unigear LS GL-3/GL-5 85W-140*Check every 500 hours, change every 1000 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 500 hours, change every 1000 hours***TRANSFERBOX VGR 13100**

Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2032*Change every 2000 hours*

BELL EQUIPMENT ARTICULATED DUMP TRUCKS B-C-D-E SERIES B25DN MK 7 (6X6) MERCEDES-BENZ OM926LA (STAGE

**TRANSMISSION** Allison 3000P ORS 6/1

Capacity: 36 liter (Dry fill), Capacity: 24 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 2000 hours

TRANSMISSION ZF 6HP592C 6/1

Capacity: 30 liter (Dry fill), Capacity: 10-15 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 1000 hours

HYDRAULIC SYSTEM

Capacity: 120 liter (Hydraulic system including tank), Capacity: 85 liter (Hydraulic tank)

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 30	Multifleet SCD 10W	

Change every 3000 hours

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

COOLING SYSTEM

Capacity: 28 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.