PRODUCT RECOMMENDATION

CASE WHEELED LOADERS 1021F FPT F2CFE614C TIER 4I/STAGE IIIB (2012-2016)

ENGINE FPT F2CFE614C
Capacity: 28,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	**Agrisynth MSP 10W-40**	**Agridiesel MSP 15W-40**

Check every 10 hours, change every 500 hours

DIFFERENTIAL FRONT ZF MT-L3105-II
Capacity: 3,7 liter (Axle cooler), Capacity: 45,7 liter (Including axle cooler)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT ZF MT-L3115-II
Capacity: 3,7 liter (Axle cooler), Capacity: 65,7 liter (Including axle cooler)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR ZF MT-L3105-II
Capacity: 3,7 liter (Axle cooler), Capacity: 45,7 liter (Including axle cooler)

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR ZF MT-L3115-II
Capacity: 3,7 liter (Axle cooler), Capacity: 65,7 liter (Including axle cooler)

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION POWERSHIFT ZF 4/3
Capacity: 45,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Agrifluid HT**

Check every 50 hours, change every 1000 hours

USE	CLIMATE
Severe (alternative)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Agrifluid HT**

Check every 50 hours, change every 500 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CASE WHEELED LOADERS 1021F FPT F2CFE614C TIER 4I/STAGE IIIB (2012-2016)

HYDRAULIC SYSTEM
Capacity: 134 liter (Hydraulic tank), Capacity: 250 liter (System)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus Biosynth 46	**Perlus H 46**	

Check every 50 hours, change every 2000 hours

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM
Capacity: 56,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	**Coolant SP 12**	**Coolant -38 Organic NF**

Check every 50 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367