

# CASE WHEELED LOADERS 421B PERKINS

## 1004-4T (1995-2001)



**ENGINE** Perkins 1004.T4  
Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Dieselfleet CD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

*Change every 250 hours*

### DIFFERENTIAL FRONT

Capacity: 3,85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Unigear LS GL-3/GL-5 85W-140**

*Change every 1000 hours*

### DIFFERENTIAL FRONT AND REAR

Capacity: 16 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Unigear LS GL-3/GL-5 85W-140**

*Change every 1000 hours*

### DIFFERENTIAL REAR

Capacity: 3,85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Unigear LS GL-3/GL-5 85W-140**

*Change every 1000 hours*

### HUB REDUCTIONS

Capacity: 2,2 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Unigear LS GL-3/GL-5 85W-140**

*Change every 1000 hours*

# CASE WHEELED LOADERS 421B PERKINS

## 1004-4T (1995-2001)



**TRANSMISSION** Powershift  
Capacity: 17,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Kroontrak MTH 10W-30</b>	<b>Synfleet SHPD 10W-40</b>	<b>Multifleet SHPD 10W-40</b>

*Change every 1000 hours*

### HYDRAULIC SYSTEM

Capacity: 65 liter (Hydraulic tank), Capacity: 80 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrifluid Synth XHP Ultra</b>	<b>Agrifluid HT-Plus</b>	<b>Agrifluid HT</b>

*Change every 2000 hours*

### HYDRAULIC BRAKE SYSTEM

Capacity: 1,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Change every 24 months*

### COOLING SYSTEM

Capacity: 24 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.