

# CASE WHEELED LOADERS 721E CASE, 4. GEN., 667TA/EED, TIER-III (2007-2011)



**ENGINE** Case 667TA/EED Tier 3  
Capacity: 14,2 liter, Filter capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 500 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 10 hours, change every 100 hours*

## DIFFERENTIAL FRONT

Capacity: 30,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## DIFFERENTIAL REAR

Capacity: 23,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## HUB REDUCTIONS FRONT

We are unable to give a standard recommendation for this component. Please contact our service department.

## HUB REDUCTIONS REAR

We are unable to give a standard recommendation for this component. Please contact our service department.

## TRANSMISSION 4F/3R Electronic 4/3

Capacity: 25,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agridiesel CRD+ 15W-40</b>	<b>Dieselfleet CD+ 15W-40</b>	<b>Multifleet SHPD 15W-40</b>

*Check every 50 hours, change every 1000 hours*

# CASE WHEELED LOADERS 721E CASE, 4. GEN., 667TA/EED, TIER-III (2007-2011)



## HYDRAULIC SYSTEM

Capacity: 106 liter (Hydraulic tank), Capacity: 176 liter (Total)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Check every 50 hours, change every 2000 hours*

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2***Change every 100 hours*

## COOLING SYSTEM

Capacity: 36,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26***Check every 50 hours, change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.