

# CATERPILLAR BULLDOZERS/TRACKED TRACTORS D6N XL 3126B ATAAC (2003-2007)



**ENGINE** 3126B ATAAC  
Capacity: 26 liter

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Normal                        |                               | Mediterranean                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

*Check every 10 hours, change every 3 months/ 500 hours*

| USE                         |                               | CLIMATE  |
|-----------------------------|-------------------------------|----------|
| Normal                      |                               | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      |          |
| <b>Agrisynth LSP 10W-40</b> | <b>Multifleet SHPD 10W-40</b> |          |

*Check every 10 hours, change every 3 months/ 500 hours*

| USE                           |                               | CLIMATE       |
|-------------------------------|-------------------------------|---------------|
| Alternative (acceptable)      |                               | Mediterranean |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      |               |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |               |

*Check every 10 hours, change every 3 months/ 500 hours*

| USE                         |                               | CLIMATE                       |
|-----------------------------|-------------------------------|-------------------------------|
| Alternative (acceptable)    |                               | Moderate                      |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Synfleet SHPD 10W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 10W-40</b> |

*Check every 10 hours, change every 3 months/ 500 hours*

**TRANSMISSION**  
Capacity: 144 liter

| USE                      |                          | CLIMATE       |
|--------------------------|--------------------------|---------------|
| Normal                   |                          | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |               |
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |               |

*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

| USE                       |  | CLIMATE |
|---------------------------|--|---------|
| Normal                    |  | Cold    |
| PRODUCT RECOMMENDATION 1  |  |         |
| <b>Gear Oil Alcat 10W</b> |  |         |

*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

# CATERPILLAR BULLDOZERS/TRACKED TRACTORS D6N XL 3126B ATAAC (2003-2007)



## HYDRAULIC IMPLEMENT SYSTEM

Capacity: 65 liter

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Normal                        |                               | Moderate                      |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Check every 10 hours, change every 2000 hours/ 12 months

## HYDRAULIC SYSTEM

Capacity: 29,5 liter (Hydraulic tank)

| USE                           |                               | CLIMATE                       |
|-------------------------------|-------------------------------|-------------------------------|
| Normal                        |                               | Moderate                      |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Dieselfleet CD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Check every 100 hours, change every 12 months/ 2000 hours

## GREASE POINTS/NIPPLES

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>MoS2 Grease EP 2</b>  |  |          |

## COOLING SYSTEM

Capacity: 48,4-54 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 17</b>     |  |          |

Check every 10 hours, change every 72 months/ 6000 hours

# CATERPILLAR BULLDOZERS/TRACKED TRACTORS D6N XL 3126B ATAAC (2003-2007)



## RECOIL SPRING COMPARTMENT

Capacity: 29,9 liter (each)

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Gear Oil Alcat 50</b> |  |  |

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

|                          |  |  |
|--------------------------|--|--|
| PRODUCT RECOMMENDATION 1 |  |  |
| <b>Gear Oil Alcat 30</b> |  |  |

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

|                           |  |  |
|---------------------------|--|--|
| PRODUCT RECOMMENDATION 1  |  |  |
| <b>Gear Oil Alcat 10W</b> |  |  |

## TRAVEL REDUCTION UNIT

Capacity: 7 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

|                          |                          |  |
|--------------------------|--------------------------|--|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
| <b>Gear Oil Alcat 30</b> | <b>Gear Oil Alcat 50</b> |  |

*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

| USE    | CLIMATE |
|--------|---------|
| Normal | Arctic  |

|                           |  |  |
|---------------------------|--|--|
| PRODUCT RECOMMENDATION 1  |  |  |
| <b>Gear Oil Alcat 10W</b> |  |  |

*Check every 1 months/ 250 hours, change every 12 months/ 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.