CATERPILLAR RIGID DUMP TRUCKS 772

(2008-2013)



| ENGINE C18 Acert MEUI Capacity: 64 liter | | | |
|---|--------------------------|---------------|--|
| USE | | CLIMATE | |
| Preferred | | Mediterranean | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Agridiesel MSP 15W-40 | Dieselfleet MSP 15W-40 | | |

Check every 10 hours, change every 3 months/ 500 hours

| USE | | CLIMATE |
|------------------------------|----------------------------|--------------------------|
| Preferred | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP Ultra FE 5W-30 | Agrisynth LSP Ultra 10W-40 | Agrisynth MSP 10W-40 |

Check every 10 hours, change every 3 months/ 500 hours

| USE | CLIMATE |
|--------------------------|---------------|
| Normal | Mediterranean |
| PRODUCT RECOMMENDATION 1 | |
| Dieselfleet MSP 15W-40 | |

Check every 10 hours, change every 3 months/ 500 hours

| USE | | CLIMATE |
|------------------------------|----------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrisynth LSP Ultra FE 5W-30 | Agrisynth LSP Ultra 10W-40 | Agrisynth MSP 10W-40 |

Check every 10 hours, change every 3 months/ 500 hours

| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |
|--------------------------|--------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Alternative (acceptable) | | Mediterranean |
| USE | | CLIMATE |

Check every 10 hours, change every 3 months/ 500 hours

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Alternative (acceptable) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agrisynth LSP 10W-40 | Multifleet SHPD 10W-40 | |

Check every 10 hours, change every 3 months/ 500 hours

DIFFERENTIAL REARCapacity: 114 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

CATERPILLAR RIGID DUMP TRUCKS 772

(2008-2013)



| ŀ |
|----|
| 1 |
| U |
| В |
| R |
| ΞD |
| U |
| CT |
| Ю |
| Ν |
| S |
| R |
| EΑ |
| R |

Capacity: 22,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

| TRANSMISSION + TORQUE CONVERTER Capacity: 95 liter | | |
|---|------------------|---------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |
| Check every 10 hours, change every 6 mo | nths/ 1000 hours | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Check every 10 hours, change every 6 months/ 1000 hours | | |

| HYDRAULIC SYSTEM HOIST + BRAKE Capacity: 130 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 10W | | |
| Charle avant 10 hours abance avant 6 | | |

Check every 10 hours, change every 6 months/ 1000 hours

WHEEL BEARINGS FRONT

Capacity: 2,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

| COOLING SYSTEM Capacity: 114 liter | | |
|---|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 17 | | |
| Check every 10 hours, change every 72 months/ 12000 hours | | |

CATERPILLAR RIGID DUMP TRUCKS 772

(2008-2013)



| HYDRAULIC SYSTEM STEERING Capacity: 50 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Oil Alcat 30 | | |
| Check every 10 hours, change every | 6 months/ 1000 hours | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel CRD+ 15W-40 | Dieselfleet CD+ 15W-40 | Multifleet SHPD 15W-40 |
| Check every 10 hours, change every | 6 months/ 1000 hours | · |
| USE | | CLIMATE |
| Biodegradable oil | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Perlus Biosynth 46 | | |
| Check every 10 hours, change every | 6 months/ 1000 hours | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.