

CATERPILLAR RIGID DUMP TRUCKS 773F EXD (2006-2012)



ENGINE C27 Acert
Capacity: 95 liter

USE	CLIMATE
Preferred	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agridiesel MSP 15W-40	Dieselfleet MSP 15W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Preferred	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Alternative (acceptable)	Mediterranean

PRODUCT RECOMMENDATION 1	
Dieselfleet MSP 15W-40	

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Alternative (acceptable)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra FE 5W-30	Agrisynth LSP Ultra 10W-40	Agrisynth MSP 10W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Acceptable	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Dieselfleet CD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 3 months/ 500 hours

USE	CLIMATE
Acceptable	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Agrisynth LSP 10W-40	Multifleet SHPD 10W-40

Check every 10 hours, change every 3 months/ 500 hours

DIFFERENTIAL REAR
Capacity: 151 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

CATERPILLAR RIGID DUMP TRUCKS 773F EXD (2006-2012)



TRANSMISSION + TORQUE CONVERTER

Capacity: 61 liter (Complete)

USE	CLIMATE
Flexible (max)	Mediterranean

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 30*Check every 10 hours, change every 6 months/ 1000 hours*

USE	CLIMATE
Flexible (max)	Cold

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 10 hours, change every 6 months/ 1000 hours*

HYDRAULIC SYSTEM HOIST + BRAKE

Capacity: 130 liter (Hydraulic tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Oil Alcat 10W*Check every 10 hours, change every 6 months/ 1000 hours*

CENTRAL LUBRICATION SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

FAN DRIVE BEARINGS

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

MoS2 Grease EP 2

USE	CLIMATE
Light Duty	Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

CATERPILLAR RIGID DUMP TRUCKS 773F EXD (2006-2012)

**WHEEL BEARINGS FRONT**

Capacity: 3,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 174 liter

USE

Extended

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 17**

Check every 10 hours, change every 36 months/ 6000 hours

POWER STEERING HYDRAULIC SYSTEM

Capacity: 38 liter (Hydraulic tank)

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Gear Oil Alcat 30**

Check every 10 hours, change every 6 months/ 1000 hours

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Agrifluid HT-Plus****PRODUCT RECOMMENDATION 3****Kroontrak MTH 10W-30**

Check every 10 hours, change every 6 months/ 1000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.