PRODUCT RECOMMENDATION

CATERPILLAR RIGID DUMP TRUCKS 775D
(1998-2001)

ENGINE 3412E
Capacity: 68 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Synfleet SHPD 10W-40**	**Dieselfleet CD+ 15W-40**

Change every 250 hours

DIFFERENTIAL REAR
Capacity: 155 liter (+ hub reductions)

We are unable to give a standard recommendation for this component. Please contact our service department.

FINAL DRIVES

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION Powershift
Capacity: 72 liter (Complete), Capacity: 53 liter (only sump)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gear Oil Alcat 30	**Gear Oil Alcat 50**	

Check every 500 hours, change every 1000 hours

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

Check every 500 hours, change every 1000 hours

HYDRAULIC SYSTEM HOIST + BRAKE
Capacity: 307 liter (Complete), Capacity: 133 liter (Hydraulic tank)

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 30		

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Gear Oil Alcat 10W		

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

CATERPILLAR RIGID DUMP TRUCKS 775D
(1998-2001)

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM
Capacity: 151 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 17		

HYDRAULIC SYSTEM STEERING
Capacity: 60 liter (Complete), Capacity: 34 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	**Kroontrak MTH 10W-30**	**Synfleet SHPD 10W-40**

SUSPENSION CYLINDERS

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367